



IPON SISTEM

Generalni zastupnik i uvoznik
projektovanje, tehnička ugradnja i
servis

FirePro®


KATALOG



Generators aerosola za gašenje požara



 <p>FirePro® FP- 100S</p>	TEHNIČKI PODACI	
	Model <i>FirePro®</i>	FP-100S
	Stanje aerosola	Hladan
	Način aktiviranja	Termički , termičko uže Električni (6-36V D/C 0,8A u 3-4 sec)
	Tip aktivatora	Grejači element električnog otpora 2,3 oma
	Struja testiranja	maksimalno 5 mA.
	Težina bruto	1370 grama
	Težina neto	100 grama
	Vreme pražnjenja	5 -10 sekundi
	Raspršivač	opcija
	Izlazni otvori	1
	Dužina mlaza aerosola	1 m
	Dimenzije	155 mm x 84 mm (uključujući kučište konektora)
	Temperatura samoaktiviranja	300°C
	Klasa požara SRPS EN2	A (čvrste materije) 0.88 m ³ B (tečnosti) 0.93 m ³ C (gasovi) 1.62 m ³ F (ulja, masti) 0.64 m ³
MOGUĆNOST UPOTREBE		
<ul style="list-style-type: none"> Zaštita prostora do 1 m³ U prevozu Merna oprema Veliki rasklopni ormari Ormari Transformatori veliki industrijski 	<ul style="list-style-type: none"> serveri, veće telefonske centrale, automobili, kamioni, autobusi, vozovi, metro, tramvaji Merni ormari, sefovi Merni ormari, upravljačke jedinice Električni ormari 	

 <p>FirePro® FP-200S</p>	TEHNIČKI PODACI	
	Model <i>FirePro®</i>	FP-200S
	Stanje aerosola	Hladan
	Način aktiviranja	Termički, termičko uže Električni (6-36V D/C 0,8A u 3-4 sec)
	Tip aktivatora	Grejači element električnog otpora 2,3 oma
	Struja testiranja	maksimalno 5 mA.
	Težina bruto	1840 grama
	Težina neto	200 grama
	Vreme pražnjenja	5-10 sekundi
	Raspršivač	opcija
	Izlazni otvori	1
	Dužina mlaza aerosola	2 m
	Dimenzije	185 mm x 84 mm (sa kučištem konektora)
	Temperatura samoaktiviranja	300 °C
	Klasa požara SRPS EN2	A (čvrste materije) 1.69 m ³ B (tečnosti) 1.80 m ³ C (gasovi) 3.13 m ³ F (ulja, masti) 1.23 m ³
MOGUĆNOST UPOTREBE		
<ul style="list-style-type: none"> Zaštita prostora do 2 m³ Skladišta Ormari Električni ormari Transformatori (veliki) Industrija Velika rasklopna postrojenja 	<ul style="list-style-type: none"> serverske sobe, spuštene plafoni, dvostruki podovi automobili, kamioni, autobusi, vozovi, metro, tramvaji ormari, trezori (sefovi) merni ormari, upravljačke jedinice U prevozu 	

<p>FirePro® Komplet za automobile</p> 	TEHNIČKI PODACI	
	Model <i>FirePro®</i>	Komplet za automobile
		FP-40S
	Stanje aerosola	Hladan
	Način aktiviranja	Termički , termičko uže Električni (6-36V D/C 0,8A u 3-4 sec)
	Tip aktivatora	Grejači element električnog otpora 2,3 oma
	Struja testiranja	Maximum 5 mA
	Težina bruto	610 grama
	Težina neto	40 grama
	Vreme pražnjenja	5-10 sekundi
	Izlazni otvori	2
	Dužina mlaza aerosola	1,2 m
	Dimenzije	140 mm x 51 mm (dijametar)
	Temperatura samoaktiviranja	300°C
Klasa požara SRPS EN2	A, B, C, F	
MOGUĆNOST UPOTREBE		
<ul style="list-style-type: none"> • Zaštita motora • Zastita kutije osiguraca 		

<p>FirePro® Komplet za autobus</p>  	TEHNIČKI PODACI	
	Model <i>FirePro®</i>	Komplet za autobus
		FP-200S
	Stanje aerosola	Hladan
	Način aktiviranja	Termički Električni (6-36V D/C 0,8A u 3-4 sec)
	Tip aktivatora	Grejači element električnog otpora 2,3 oma
	Struja testiranja	maksimalno 5 mA.
	Težina bruto	1840 grama
	Težina neto	200 grama
	Vreme pražnjenja	5-10 sekundi
	Raspršivač	opcija
	Izlazni otvori	1
	Dužina mlaza aerosola	2 m
	Dimenzije	185 mm x 84 mm (sa kućištem konektora)
Temperatura samoaktiviranja	300 °C	
Klasa požara SRPS EN2	A, B, C, F	
MOGUĆNOST UPOTREBE		
<ul style="list-style-type: none"> • Zaštita motora autobusa • Zastita web grejanja • Zastita elektro kablova • Zastita kutije za osigurace 		

